



AX (AXW) 型推力滚针和保持架组件

Thrust Needle Roller and Cage Assemblies

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation	外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		极限转速 Limiting Speed (rpm)		重量 Weight (Kg)
		Dc1	Dc	H、(H1/H2)	动Cr Dynamic	静Cor Static	脂润滑 Grease	油润滑 Oil	
6.5	SZ-926	6.5	17	6.745	5500	13300	6400	18400	0.0088
7.1	AX 7 15	7.1	15	2.3	3100	3250	6400	18400	0.0016
8	AX 8 16	8	16	2.3	3100	7900	6300	18000	0.0017
10	AX 10 22	10	22	2.8	6200	15300	4700	13700	0.00437
	AX 4 10 22	10	22	4	6200	15300	4700	13700	0.0068
15	AX 4 15 28	15	28	4	8100	26900	3600	10300	0.0098
17	81703/YA	17	37	7	16500	53800	4000	10000	0.03164
20	7589104	20	35	7	10270	17260	6000	8500	0.0303
25	AX 5 25 42	25	42	5	13100	58000	2300	6600	0.0257
27	AX 27 44	27	44	2.8	13700	61900	2200	6200	0.0127
29.5	SZ-920	29.5	50	3.58	27000	39000	2000	5700	0.0300
30	AXW 30	30	50	4 / 3.2	14700	69600	2000	57000	0.0252
35	AXW 35	35	55	4 / 3.2	16700	85000	1700	5000	0.0268
40	AX 40 60	40	60	2.8	19700	109200	1500	4400	0.0239
45	AX 45 65	45	65	2.8	21000	123500	1400	4000	0.0247
	SZ-905	45	65	12	29800	128000	1400	4000	0.14101

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation	外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		极限转速 Limiting Speed (rpm)		重量 Weight (Kg)
		Dc1	Dc	H、(H1/H2)	动Cr Dynamic	静Cor Static	脂润滑 Grease	油润滑 Oil	
55.45	SZ-916	55.45	79.8	4.775	30800	156400	1400	4000	0.05384
55.5	SZ-924	55.5	77	4.75	26900	130900	1400	4000	0.04919
68.15	SZ-917	68.15	92.5	4.775	33400	187700	1200	3000	0.07100